

10/708,749

3

BOE 0472 PA

In The Claims:

1. (Original) A shower system comprising:
a shower stall comprising a sidewall, a ceiling, and a base, said shower stall defining a shower area;
a shower stall housing enclosing said shower stall, wherein an air channel is defined between said shower stall and said shower stall housing;
at least one misting nozzle positioned within said shower stall; and
a controller directing misted air through said at least one misting nozzle, said controller further activating an air flow system such that misted air within said shower area flows through and is dried in said air channel.
2. (Original) The system of claim 1, wherein said shower stall comprises a cylindrical, cubicle, conical, or irregular shape defining said shower area.
3. (Original) The system of claim 1 further comprising a user accessible water input tank receiving water from a user prior to said user taking a shower.
4. (Original) The system of claim 1 further comprising an input display, wherein commands are entered for at least one of user height or user desired temperature.
5. (Original) The system of claim 1, wherein said controller receives at least one of: a height of user signal, a temperature within said shower area signal, or a distance signal and adjusts said at least one misting nozzle as a function thereof.

10/708,749

4

BOE 0472 PA

6. (Original) The system of claim 5 further comprising at least one height sensor generating a height of user signal.

7. (Original) The system of claim 5 further comprising at least one temperature sensor generating a temperature within said shower area signal.

8. (Original) The system of claim 5 at least one distance sensor generating a distance signal as a function of a distance between said at least one misting nozzle and a user.

9. (Original) The system of claim 1 further comprising at least one water pipe feeding said at least one misting nozzle.

10. (Original) The system of claim 1 further comprising a plurality of misting nozzles.

11. (Original) The system of claim 10 further comprising a first number of said plurality of misting nozzles on a first row receiving water from said pipe.

12. (Original) The system of claim 11 further comprising a second number of said plurality of misting nozzles mounted on a second row receiving water from said pipe.

13. (Original) The system of claim 12 further comprising a third number of said plurality of misting nozzles mounted on a third row receiving water from said pipe.

10/708,749

5

BOE 0472 PA

14. (Original) The system of claim 12 further comprising a controller activating said first row of misting nozzles and said second row of misting nozzles when a user is within a first height range and activating only said second row of misting nozzles when said user is within a second height range.

15. (Original) The system of claim 1, wherein said base defines at least one opening for receiving mist.

16. (Original) The system of claim 15, wherein said base is perforated.

17. (Original) The system of claim 1, wherein sides of said shower stall and said shower stall housing comprise at least one condensing surface.

18. (Original) The system of claim 1 further comprising a drain receiving water from said condensed surfaces.

19. (New) The system of claim 1, wherein said controller further comprises logic for activating a misting cycle wherein a mist is directed out of said at least one misting nozzle for a passenger selectable time period within a first predetermined time period, activating a soaping cycle for a passenger selectable time period within a second predetermined time period, activating a rinsing cycle for a passenger selectable time period within a fourth predetermined time period, activating a drying cycle for a passenger selectable time period within a fourth predetermined time period, and activating a cleaning cycle in response to the user leaving said shower area for a fifth predetermined time period.

10/708,749

6

BOE 0472 PA

20. (New) The system of claim 19, wherein said first time period is less than 60 seconds, said second time period is less than 240 seconds, said third time period is less than 600 seconds, said fourth time period is less than 600 seconds, and said fifth time period is less than 90 seconds.

[19.] 21. (Currently Amended) An airplane shower system comprising:

a changing area;

a shower stall adjacent to said changing area such that a user enters said shower stall directly from said changing area, said shower stall substantially cylindrical in shape and comprising,

a primary wall comprising a sidewall comprising an interior surface and an exterior surface, a ceiling and a base, said interior surface of said primary wall defining a shower area, said interior surface comprising a hydrophobic surface, said exterior surface comprising a first condensing surface,

a secondary wall comprising an inner surface, said inner surface of said secondary wall comprising a second condensing surface, wherein an air channel is defined between said exterior surface of said primary wall and said inner surface of said secondary wall such that water within mist flowing through said air channel condenses on said first condensing surface and said second condensing surface;

a first row of misting nozzles coupled to said primary wall such that said first row of misting nozzles direct mist into said shower area at multiple angles with respect to a central area of said shower area, wherein said central area is substantially trans-axial to said shower stall;

a second row of misting nozzles coupled to said primary wall below said first row of misting nozzles such that said second row of misting nozzles direct mist into said shower area;

a fan coupled to said shower stall;

10/708,749

7

BOE 0472 PA

a controller activating said first row of misting nozzles and said second row of misting nozzles when a user is within a first height range and activating said second row of misting nozzles when said user is within a second height range, said controller further controlling said fan, thereby blowing misted air out of said shower area and through said base whereby said misted air flows through said air channel.

[20.] 22. (Currently Amended) The system of claim [19] 21, wherein said primary wall comprises a cylindrical, cubicle, conical, or irregular shape defining said shower area.

[21.] 23. (Currently Amended) The system of claim 19 further comprising a user accessible water input tank receiving water from a user prior to said user taking a shower.

[22.] 24. (Currently Amended) The system of claim [19] 21 further comprising an input display wherein commands are entered for at least one of user height or user desired temperature.

[23.] 25. (Currently Amended) The system of claim [19] 21 further comprising at least one height sensor generating a height of user signal.

[24.] 26. (Currently Amended) The system of claim [19] 21 further comprising at least one temperature sensor generating a temperature within said shower area signal.

[23.] 27. (Currently Amended) The system of claim [19] 21 at least one distance sensor generating a signal as a function of a distance between at least one of said plurality of misting nozzles and a user.

10/708,749

8

BOE 0472 PA

[24.] 28. (Currently Amended) The system of claim [19] 21 further comprising at least one water pipe feeding said plurality of misting nozzles.

[25.] 29. (Currently Amended) The system of claim 19 further comprising a third number of said plurality of misting nozzles mounted on a third row receiving water from said pipe.

[26.] 30. (Currently Amended) The system of claim [19] 21, wherein said base defines at least one opening for receiving mist.

[27.] 31. (Currently Amended) The system of claim [19] 21, wherein said base is perforated.

[28.] 32. (Currently Amended) The system of claim [27] 31 further comprising a drain receiving water from said condensed surfaces.

[29.] 33. (Currently Amended) A method for operating a shower system having a shower area for showering of a user comprising:

- receiving a height signal based on a height of the user;
- activating a plurality of nozzles as a function of said height signal;
- activating a misting cycle wherein a mist is directed out of said nozzles;
- activating a soaping cycle;
- activating a drying cycle;
- activating a cleaning cycle in response to the user leaving the shower area; and

10/708,749

9

BOE 0472 PA

blowing air into the shower area, thereby forcing misted air out of the shower area and into an air channel defined by at least one condensing surface.

[30.] 34. (Currently Amended) The method of claim [29] 33 further comprising receiving user inputted water.

[31.] 35. (Currently Amended) The method of claim [29] 33, wherein activating said soaping cycle further comprises pausing said misting cycle.

[32.] 36. (Currently Amended) The method of claim [29] 33 further comprising recycling at least a portion of said air through said shower area.

[33.] 37. (Currently Amended) A shower system for showering of a user comprising:

- a primary wall comprising a sidewall comprising an interior surface and an exterior surface, a ceiling and a base, said interior surface of said primary wall defining a shower area, said interior surface comprising a hydrophobic surface, said exterior surface comprising a first condensing surface;

- a secondary wall comprising an inner surface, said inner surface of said secondary wall comprising a second condensing surface, wherein an air channel is defined between said exterior surface of said primary wall and said inner surface of said secondary wall such that water within mist flowing through said air channel condenses on said first condensing surface and said second condensing surface;

- a first row of misting nozzles coupled to said primary wall such that said first row of misting nozzles direct mist into said shower area at multiple angles with respect to a central area of said shower area, wherein said central area is substantially trans-axial to said shower stall;

10/708,749

10

BOE 0472 PA

a second row of misting nozzles coupled to said primary wall below said first row of misting nozzles such that said second row of misting nozzles direct mist into said shower area;

a fan coupled to at least a portion of at least one of said ceiling or said base; and

a controller comprising logic for receiving a height signal based on a height of the user, activating said first row of misting nozzles and said second row of misting nozzles as a function of said height signal, activating a misting cycle wherein a mist is directed out of said first row of misting nozzles and said second row of misting nozzles, activating a soaping cycle, activating a drying cycle, activating a cleaning cycle in response to the user leaving said shower area, and blowing air into said shower area, thereby forcing misted air out of said shower area and into said air channel.

[34.] 38. (Currently Amended) The system of claim [33] 37 further comprising a user accessible water input tank receiving water from the user prior to the user taking a shower.

[35.] 39. (Currently Amended) A shower system for a vehicle comprising:

a changing area;

a shower stall adjacent to said changing area such that a user enters said shower stall directly from said changing area, said shower stall comprising,

a primary wall comprising a sidewall comprising an interior surface and an exterior surface, a ceiling and a base, said interior surface of said primary wall defining a shower area, said interior surface comprising a hydrophobic surface,

a secondary wall comprising an inner surface, wherein an air channel is defined between said exterior surface of said primary wall and said inner surface

10/708,749

11

BOE 0472 PA

of said secondary wall such that water within mist flowing through said air channel condenses within said air channel;

a first row of misting nozzles coupled to said primary wall such that said first row of misting nozzles direct mist into said shower area at multiple angles with respect to a central area of said shower area;

a fan coupled to said shower stall; and

a controller activating said first row of misting nozzles when a user is within a first height range, said controller further controlling said fan, thereby blowing misted air out of said shower area and through said base whereby said misted air flows through said air channel.

[36.] 40. (Currently Amended) The system of claim [35] 39 further comprising a second row of misting nozzles coupled to said primary wall below said first row of misting nozzles such that said second row of misting nozzles direct mist into said shower area.

[37.] 41. (Currently Amended) The system of claim [36] 40, wherein said controller activates said second row of misting nozzles when a user is within a second height range.

[38.] 42. (Currently Amended) The system of claim [36] 40, wherein at least one of said inner surface of said secondary wall, said exterior surface of said primary wall, or an exterior surface of said base comprise a condensing surface.

[39.] 43. (Currently Amended) The system of claim [36] 40 further comprising a user accessible water input tank receiving water from a user prior to said user taking a shower.

10/708,749

12

BOE 0472 PA

[40.] 44. (Currently Amended) The system of claim [36] 40, wherein the controller further comprises logic for activating a misting cycle wherein a mist is directed out of said first row of misting nozzles, activating a soaping cycle, activating a drying cycle, and activating a cleaning cycle in response to the user leaving said shower area.

[41.] 45. (Currently Amended) The system of claim [36] 40 wherein said controller activates a third row of misting nozzles and a fourth row of misting nozzles when a user is within a third height range and a fourth height range respectively.

46. (New) The system of claim 39, wherein the controller further comprises logic for activating a misting cycle wherein a mist is directed out of said first row of misting nozzles for a passenger selectable time period within a first predetermined time period, activating a soaping cycle for a passenger selectable time period within a second predetermined time period, activating a rinsing cycle for a passenger selectable time period within a fourth predetermined time period, activating a drying cycle for a passenger selectable time period within a fourth predetermined time period, and activating a cleaning cycle in response to the user leaving said shower area for a fifth predetermined time period.

47. (New) The system of claim 46, wherein said first time period is less than 60 seconds, said second time period is less than 240 seconds, said third time period is less than 600 seconds, said fourth time period is less than 600 seconds, and said fifth time period is less than 90 seconds.